

1967 Corvette: Service News: Corvette Door Window Removal

Subject: Corvette Door Window Removal

Model and Year: 1967 Corvette

Source: Chevrolet Service News

Number: Volume 39, Issue Number 9

Date: August 1967, Page 2

The 1967 Corvette Door window glass can be removed without removing the ventilator assembly as presently outlined on page 1B-13 of the 1967 (Passenger Car) Chassis Service Manual if the following procedure is followed.

1. Remove two screws under arm rest.
2. Using Tool J-7797, remove clips retaining window crank and lock remote control.
3. Remove knob from door lock control by turning counter clockwise.
4. Remove 2 screws retaining inside pull handle.
5. Remove sheet metal screws and special washers retaining trim panel to door assembly.
6. Pull trim panel with hand to disengage from top of door. Remove trim panel from vehicle.
7. Remove door water deflector from inner surface.
8. With window in full-up position, remove two screws retaining rear glass run channel to panel and remove channel from bracket.
9. Lower window approximately 1 1/2" to access two (2) sash retaining nuts through openings provided in panel. Remove glass from upper guide rail and lower in door opening. Lower guide rail to full down position.
10. Rotate window within door panel 180 degrees and remove from door.

Online URL:

<https://www.corvetteactioncenter.com/tech/knowledgebase/article/1967-corvette-service-news-corvette-door-window-removal-49.html>